



By CRC Industries 

PRODUCT DATA SHEET

QGUN, 150ml Part Number: 030080



Product Description	Plastic safe lubricant, penetrant and corrosion inhibitor that helps prevent firearm malfunctions caused by water penetration, humidity, condensation, or corrosion. Q-Gun is formulated to not damage plastic components.
Applications	Q Gun is designed for a small arms, rifles and automatic military weapons and also suitable for any element or replacement element specifically and essential to its operation, including a barrel, frame, or receiver, slide or cylinder, bolt or breech block, trigger etc
Unit Package Description	150ml Aerosol
Brand	CRC (South Africa)
Generic Description I	Lubricant and Penetrant
Net Fill	120 grams
UPC Code	6001690300801
Unit Dimension	14.1H x 5.2W x 5.2D cm
Units Per Case	24
Case Dimensions	14.5H x 32.5W x 33.5L cm
Cases Per Pallet	112
Case Weight	4.1kg
Appearance	Amber Liquid
Base Type	Petroleum Distillate
Flash point (F)	>212°F
Flash point (C)	>100°C
Flammability Class - CPSC	None (Under South Africa definitions)
Spec Gravity Concentrate	0.81 to 0.84

Last revised: May 3, 2023 8:43 AM
Page: 1 of 2

CRC Industries RSA (PTY) LTD

Registration No: 2011/148738/07 | VAT No: 4750261325
Gauteng Business Park - 15/16 Brond Crescent - Clayville Ext 20 - Olifantsfontein - 1666
PO Box 1161 - Olifantsfontein - 1665
Tel: 011 452 7048 | Mail: info.sa@crcind.com | www.q20.co.za



www.crcindustries.co.za

CRC Industries is a worldwide leader in the production of speciality chemicals for maintenance and repair professionals serving industrial, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



By CRC Industries 

PRODUCT DATA SHEET



Plastic Safe	Yes
Film Type	Thin, Non-Drying
Film Thickness	Not Determined
Evaporation Rate	Slow
Dielectric Strength	55,300 Voltx
Working Temp (F)	Max 250°F
Working Temp (C)	Max 121.1°C
Propellant	Carbon Dioxide
Military Specification Number	Not Determined
Aerosol Flammability Level	I
Restricted from Sale In	Not for sale in United States
Removal (How To)	Remove with Petroleum Distillates

Last revised: May 3, 2023 8:43 AM
Page: 2 of 2

CRC Industries RSA (PTY) LTD

Registration No: 2011/148738/07 | VAT No: 4750261325
Gauteng Business Park - 15/16 Brond Crescent - Clayville Ext 20 - Olifantsfontein - 1666
PO Box 1161 - Olifantsfontein - 1665
Tel: 011 452 7048 | Mail: info.sa@crcind.com | www.q20.co.za



www.crcindustries.co.za

CRC Industries is a worldwide leader in the production of speciality chemicals for maintenance and repair professionals serving industrial, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.