



Product: Zinc Spray

Revision Number: 0

Date Issued: 09/12/2024

Page 1 of 1

TECHNICAL DATA SHEET

ZINC SPRAY

1. DESCRIPTION:

A clear colourless liquid.

2. APPLICATION:

Zinc galvanizing spray

3. BENEFITS / USEFULL CHARACTERISTICS

Corrosion prevention. Galvanise touch up. Durable resin coating. Long term protection.

4. DIRECTIONS FOR USE

Shake well before use. Shake until the agitator ball moves freely in the can. Apply to a clean, dry surface. Apply a thin even film. Best results are obtained with 2 lighter rather than 1 heavy coat. Additional coats can be applied after 15 – 20 minutes. Do not use on energized equipment. Do not use on sensitive electronic equipment. Clean the aerosol valve by turning the can upside down and spraying until only propellant escapes.

5. WARNINGS

Extremely flammable aerosol. Pressurised container: May burst if heated. Harmful in contact with skin. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe mist / vapours / spray. Use only outdoors or in a well-ventilated area. Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F. Dispose of contents / container to an authorised waste collection point.

6. PROPERTIES

Appearance:	Silver liquid.
Odour:	Characteristic.
Flammability:	Extremely Flammable
UN Code:	1950
Chemical Composition:	Zinc Galvanizing spray Dimethyl Ether
Pack size	400ml Aerosol
Units per Case	12